



Features

- Can use multiple liquid fuel types (JP-8/F-24, F-34 "NATO", gasoline, methanol, isopropanol)
- Propane Fuel Capability Add-On Option Available
- Twin Tech parallel function allows two units connected together to provide 3kW/30 AMPs of rated power.
- Lightweight, "Man Portable"
- Quiet, small noise signature
- Plug-in compatible with Trinity™ Systems or stand-alone
- Immediate functionality on startup - No waiting
- Auto turn down when load is low
- Low maintenance, Easy to operate
- 2,000 hour/1 year limited warranty (repair or replace)
- Tunable for high elevation

Includes

- 1x IntelliGEN™ 2200 Flex-Fuel Generator v1.0 (p/n INI-IG2200)
- 1x Initial Oil Fill Bottle
- 1x 12.5' Extended Exhaust Piping w/ Clamp
- 1x Parallel "Y" Cable w/ Adapter
- 1x Field Level 2kW Maintenance Kit
- 1x Operator Manual
- 2x Cold start canister (Removed for Air shipment)
- 2x Quart 10W40 Small Engine Oil
- 1x Quick Reference Card

Specs

- Start System: Manual Recoil Start
- Max Peak Output: 2200W (Sea Level) (Gasoline and JP-8/F-24)
- Gasoline Nominal Output: 1900W (Sea Level)
- Gasoline Nominal Voltage: 120VAC, 60Hz, 12VDC
- JP-8/F-24 Nominal Output:
 - Tested to 1800W
 - Certified to 1600W (Sea Level)
 - 1800W Cert Expected Q1 2022
- JP-8/F-24 Nominal Voltage: 120VAC, 60Hz, 12VDC
- AC Output Power outlets: 15A (2), 30A (1)
- DC Output Power outlets: 12V 3A (1)
- Dry Weight: 55.2 lb. (25 kg)
- Dimensions: 21.9" x 11.8" x 18.5" (557 mm x 300 mm x 470 mm)
- Gasoline Operating Temp: -4°F to 122°F (-20°C to 50°C)
- JP-8 Operating Temp: 14°F to 122°F (-10°C to 50°C)
- Storage Temp: -40°F to 176°F (-40°C to 80°C)
- Operating Elevation: Sea Level to 10,000 ft. (3048 m)
- Internal Tank: 1.2 gal (4.5 L)
- Color: Tan or Green