



Features

- Can use multiple liquid fuel types (JP-8/F-24, F-34 "NATO", gasoline, propane, methanol, isopropanol)
- One man, two man and four man maneuverable
- Quiet, small noise signature
- Plug-in compatible with Trinity TM Systems or stand-alone
- Immediate functionality on startup - no waiting
- Auto turn down when load is low
- 2,000 hour rated lifetime, low maintenance
- 2,000 hour/1 year limited warranty (repair or replace)
- Tunable for high elevation

Includes

- 1x IntelliGEN™ 5000 Flex-Fuel Generator v2.5
- 1x Initial Oil Fill Bottle
- 1x 30 Amp Splitter Cable
- 2x Spark Plug
- 1x Field Level 5kW Maintenance Kit
- 1x Operator manual
- 6x Cold Start Canister (removed for air shipment)
- 2x Quart 10W40 small engine oil
- 1x Quick Reference Card
- 1x SurePak Shipping Container

Specs

- Start System: Electric Start
- Max Peak Output: 5000W (Sea level) (Gasoline and JP-8/F-24)
- Gasoline Nominal Output: 4500-5000W (Sea level)
- Gasoline Nominal Voltage: 110-240VAC, 50 or 60Hz
- JP-8/F-24 Nominal Output: 3500-4000W (Sea level)
- JP-8/F-24 Nominal Voltage: 110-240VAC 50 or 60Hz
- AC Output Power outlets: Customer Specified
- Dry Weight: 228lbs. (104kgs)
- Dimensions: 36.7" x 26.3" x 30.2" (933mm x 669mm x 768mm)
- Gasoline Operating Temp: -4 o F to 122 o F (-20 o C to 50 o C)
- JP-8 Operating Temp: 14 o F to 122 o F (-10 o C to 50 o C)
- Storage Temp: -40 O F to 176 o F (-40 o C to 80 o C)
 - Operating Elevation: Sea level to 10,000 feet (3,048m) Internal Tank: 4.5 gallons (17 L), quick connect for XRT TM and compressed fuel
- Color: CARC Tan or Green